### Panel | Acoustic

# FR701® 2100







# FR701® 2100

### **Specifications**

Content	100% post-consumer recycled polyester	
Weight	16.0 ± 0.5 oz./lin. yd	
Width	66" min. useable	
Repeat	none	

## **Cleaning Code**

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup.

Bleach Cleanable - May be cleaned with a 10% bleachto-water solution. Rinse well after cleaning. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.

#### **Miscellaneous**

Application testing of this product is recommended. Colors may vary between dye lots. This is a nondirectional fabric.

Proudly woven in North America supporting our local communities.

## **Sustainability**

100% recycled and recyclable



#### **Performance**

WE	Col
**	Gra

orfastness to light (AATCC 16.3 Option 3) ade 4 min. at 40 hours

Colorfastness to crocking (AATCC 8) Grade 4 min. dry & Grade 3 min. wet



**Breaking Strength (ASTM D5034)** 150 lbf min. warp and fill



Flammability

ASTM E84 Class I or A

#### **Acoustical Performance**

Our acoustic fabrics are all acoustically transparent. This represents the amount of sound that passes through the fabric.

**Acoustic Transparency:** 

95%

For more detailed results, please consult our website.



This pattern is included in the underwriters laboratory panel fabric recognition program. Additional testing of this  $\dot{\text{U.L.}}$ recognized fabric is not required on approved panels from participating manufacturers.



## **Guilford of Maine**

Renowned for its exceptional performance and style, Guilford of Maine has set industry standards in acoustics and panel fabrics for many decades. We present the Guilford of Maine Collection - a selection of timeless fabrics.





For samples, visit guilfordofmaine.com