

# FAQ

## Frequently Asked Questions



Stretch Systems for Walls & Ceilings

### General Information

- FabricWall location: St. Louis, MO
- Shipping Lead Time
  - Track 1-2 days.
  - Core 1- 2 weeks
  - Standard Fabric 1-2 weeks, call for availability
  - Tucking Tools 1-2 Days

### Track

- Standard Track Length: 5'-0" ( 60" )  
Custom lengths available up to 8',  
minimum order quantities apply.
- Track Description
  - ½", model numbers start with 50, example 50MOTD, 360 LF per case
  - 5/8", model numbers start with 65, example 65MOTD, 360 LF per case
  - 1", model numbers start with 10, example 10MOTD, 315 LF per case
  - 2", model number start with 20 example 20MOTD, 110 LF per case
- Track Edge Profiles
  - Square
  - Bevel
  - Radius

[FabricWall Track Website Link](#)

[FabricWall Right Track Guide Website Link](#)

### Cores

Standard Sound Absorbing Cores

- FWAP: 6 pcf fiberglass, thickness: 1" and 2"
- FWATF: 6 pcf fiberglass, with 1/8" high density facing sheet, thickness: 1" and 2"
- FWPOLY: 100% polyester, thickness: 1" and 2"

Custom Sound Absorbing Cores

- FWBP2: designed to absorb sound evenly across all frequencies, thickness: 2" only
- FWLFA2: designed to absorb low-frequency sounds while reflecting high-frequency sounds, thickness: 2" only
- FWRAD: designed to absorb and diffuse sound, good mid-range frequency sound absorption, thickness: 1" and 2"

### Fabric

- Standard fabrics are 66" wide and available in a variety of colors. Upgrade fabrics also available.
- Extra wide fabric : VistaSpan comes 125"w and is available in White or Black, great for ceilings.
- See FabricWall website for approved fabrics [FabricWall Fabric Website Link](#)
- Contact FabricWall on custom finishes

